

SMTrue™ Smart Feeders for LE40V,

LS40V & LS60V Auto Pick & Place

SMTrue™ Smart Feeders available on 'SMART System' Automated Pick and Place Machines - Option for Models LE40V, LS40V, and LS60V.

Providing Economic Solutions for:


Prototyping
Product Development
Short Run, High-Mix
Manufacturing Applications



- Ensure the right component is placed in the right board location everytime
- Faster job setup and changeover with easy feeder plug-in and recognition
- Accurately manage and track component inventory through Smart Feeder database
- SMTrue Smart Feeders available in all feeder types including tape, bank, vibratory, matrix, and cut-tape feeders

Product Features

- Flexibility with SMTrue[™] Smart Feeders available in every feeder type - tape, bank, vibratory, matrix, and cut-tape feeders
- Tape feeders available in both bank and individual configurations
- Smart Feeder Control assigns Unique Feeder ID for each feeder
- Manage Feeder information through the Smart Feeder Database
- Link Feeder hardware to all the important component information including feeder address, position, component dimensions, count and even tape index and vibratory control.
- Control frequency and amplitude via the Smart Feeder Software or through the Smart Feeder
- Recognize the presence or absence of a feeder



SMTrue™ Smart Feeder Database

PRODUCT SPECIFICATIONS:

Specification Typical	ETF LTSXXmm Feeder	BankFeeder LBFS
Component Tape	0201, PLCC20	0201, PLCC20
Width	8, 12, 16, 24, 32, 44mm	8mm
Tape Width max. Tape	+0.3mm	+0.3mm
Thickness max. Tape	1.1mm	1.1mm
Material Tape/Feeder	Plastic, Paper, Metal	Plastic, Paper, Metal
Index Reel Size	2mm through 40mm	2mm through 4mm
	up to 331mm	up to 331mm

erStrip Feeder
0201, PLCC20
8mm
+0.3mm
15
1.1mm
ic, paper, metal

Specification	Vibratory Feeder LVFS
Typical Component	0603, SOIC, PLCC, Connectors
Tube Width	up to 100mm
Tube Capacity	up to 13 SOIC8 (max. width up to 111mm)
Max. Component Length	50mm
Tube Material	Plastic
Activation Feed	0.1 sec to 7.0 sec
Amplitude Range	0 to 100% (max. 1A)
Frequency Range	0 Hz to 120 Hz



Options

L-CL	Cyberoptics® Centering Laser
L-LD	Liquid Dispenser
L-TS	Touch Screen with Enhanced Operator Interface

Feeder Options (For Custom "Smart System Machines" only)

L-SVF	Smart Vibratory Tube/Bulk Feeder
L-ST (smart tape feeders)	8, 12, 16, 24, 32, & 44mm
L-SBF-12 (smart bank feeders)	12 lane bank feeder for 8mm tape



Phone: 215-485-5663 • Fax: 215-485-5664 • www.ddmnovastar.com • sales@ddmnovastar.com